



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/799,707	03/15/2004	Hideori Shindoh	250438US2	8967
22850	7590	03/05/2009		
OBLON, SPIVAK, MCCLELLAND MAIER & NEUSTADT, P.C. 1940 DUKE STREET ALEXANDRIA, VA 22314			EXAMINER HANG, VU B	
			ART UNIT 2625	PAPER NUMBER
			NOTIFICATION DATE 03/05/2009	DELIVERY MODE ELECTRONIC

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

patentdocket@oblon.com

oblonpat@oblon.com

jgardner@oblon.com

### Office Action Summary

**Application No.**

10/799,707

**Applicant(s)**

SHINDOH ET AL.

**Examiner**

Vu B. Hang

**Art Unit**

2625

**Period for Reply** -- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

**Status**

- 1) ☒ Responsive to communication(s) filed on 04 December 2008.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

**Disposition of Claims**

- 4) ☒ Claim(s) 1-28 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-28 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

**Application Papers**

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 15 March 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
- Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
- Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

**Priority under 35 U.S.C. § 119**

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some \* c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

**Attachment(s)**

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO-85/86)
- Paper No(s)/Mail Date 07/27/2004.
- 4) ☐ Interview Summary (PTO-413)
- Paper No(s)/Mail Date \_\_\_\_\_.
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: \_\_\_\_\_

### **DETAILED ACTION**

- This office action is responsive to the communication filed on 12/04/2008.
- The amendments received on 12/04/2008 have been entered and made of record.
- Claims 1-28 are pending in the current application.

### ***Response to Arguments***

1. Applicant's arguments filed on 12/04/2008, with respect to the cited prior art and the rejections to the amended independent Claims 1, 20, 25 and 27, have been fully considered and are persuasive. Therefore, the previous rejections of Claims 1-28 have been withdrawn. However, upon further consideration, a new ground of rejection is made in view of Mori (US Patent 6,965,453 B1).

### ***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1-2, 5 and 12-28 are rejected under 35 U.S.C. 103(a) as being unpatentable over Endo (US Patent 6,801,340 B1) in view of Mori (US Patent 6,965,453 B1), and in further view of Grosse et al. (US Patent 5,636,294).

4. Regarding **Claim 1**, Endo discloses an electronic device which receives image data across a data communication bus shared among a memory, a processing unit and the electronic

device, and converts the image data for outputting therefrom (see Fig.2 (211,201,203,205), Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), comprising: a plurality of conversion units configured to convert the image data (see Fig.3 (308), Col.5, Line 30-34 and Col.6, Line 33-36); a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); an image data transfer unit configured to transfer the image data between the control unit and at least two of the conversion units (see Fig.3 (302), Col.5, Line 30-34 and Col.5, Line 45-53). Endo fails to disclose a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data, wherein the control unit outputs the image data after a predetermined number of conversions are completed by the conversion units. Mori, however, discloses an image processor for printing image data (see Fig.1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig.1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig.1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig.1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18).

5. Endo and Mori are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data,

wherein the control unit outputs the image data after a predetermined number of conversions are completed by the conversion units. The motivation would be to convert the image data into a suitable output format for printing, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency.

6. Regarding **Claim 2**, Endo further discloses wherein the control unit supplies to one of the conversion units a signal (command) indicative of a start of transfer of the image data when transferring the image data to one of the conversion units (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50).
7. Regarding **Claim 5**, Endo further discloses wherein one of the conversion units supplies to the control unit a signal (command) indicative of a start of transfer of the converted image data to the control unit for transmitting the converted image data to a designated receiver unit (see Fig.3 (302,305,308,309) and Col.5, Line 53-56).
8. Regarding **Claim 12**, Endo further discloses wherein the control unit makes one of the conversion units convert the image data according to a request indicative of a conversion that is applied to the image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).
9. Regarding **Claim 13**, Endo further discloses wherein the control unit selects one of the conversion units according to the request so as to make the selected one of the conversion units convert the image data (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51).

10. Regarding **Claim 14**, Endo further discloses wherein the request specifies a format of the image data prior to conversion and a format of the converted image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).13. Regarding Claim 15, the rationale provided for the rejection of Claim 1 is incorporated herein.

14. Regarding Claim 16, an official notice is taken that it is known in the art that a processing hardware unit of a computer system are implemented with a program stored in a computer chip.

11. Regarding **Claim 17**, an official notice is taken that it is known in the art that the processing functions of the hardware of an image processing computer system are implemented on printed circuit boards that are connectable to an upper-order apparatus such as a scanner unit or a multifunction peripheral device.

16. Regarding Claim 18, Endo further discloses wherein the image data is received from the upper-order apparatus, and the converted image data is output to the upper-order apparatus (see Fig.3 (302,305,308,309) and Col.4, Line 22-28).

12. Regarding **Claim 19**, Endo further discloses wherein the control unit is also configured to convert the image data (see Fig.3 (308) and Col.5, Line 45-53).

13. Regarding **Claim 20**, Endo discloses an image forming apparatus (see Fig.3, Col.3, Line 28-44 and Col.3, Line 57-66), comprising: hardware resources configured to form images (see Fig.2 and Col.3, Line 28-44); a memory having a program stored therein for causing the hardware resources to form the images (see Fig.2, Col.3, Line 28-44 and Col.8, Line 39-43); a central processing unit (see Fig.2 (201)); a data communication bus shared among the memory, the processing unit and the electronic device (see Fig.2 (211,201,203,205); and an electronic device which receives image data, and converts the image data for outputting therefrom (see

Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), comprising: a plurality of conversion units configured to convert the image data (see Fig.3 (308), Col.5, Line 30-34 and Col.6, Line 33-36); a control unit configured to control the conversion units, and configured to output and receive the image data to/from the data communication bus (see Fig.2 (211,205,207,208,209,210), Fig.3 (308) and Col.5, Line 45-53); an image data transfer unit configured to transfer the image data between the control unit and at least two of the conversion units (see Fig.3 (302), Col.5, Line 30-34 and Col.5, Line 45-53). Endo fails to disclose a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data, wherein the control unit outputs the image data after a predetermined number of conversions are completed by the conversion units. Mori, however, discloses an image processor for printing image data (see Fig.1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig.1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig.1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig.1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18).

14. Endo and Mori are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a clock unit configured to provide synchronization between the control unit and at least two of the conversion units for transfer of image data, wherein the control unit outputs the image data after a predetermined number of conversions are

completed by the conversion units. The motivation would be to convert the image data into a suitable output format for printing, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency.

15. Regarding **Claim 21**, Endo further discloses a conversion request generating unit which generates a conversion request, wherein the electronic device converts the image data in response to the conversion request (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35).

16. Regarding **Claim 22**, Endo further discloses a conversion type specifying unit which generates information about a format of the image data prior to conversion and a format of the image data after the conversion (see Fig.4 and Col.4, Line 38-48), the information being supplied to the conversion request generating unit (see Col.6, Line 18-28 and Col.6, Line 33-35).22.

Regarding **Claim 23**, Endo further discloses wherein the request generating unit generates the conversion request responsive to the information supplied to the from the conversion type specifying unit (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33- 35).

17. Regarding **Claim 24**, Endo further discloses a memory area allocating unit which allocates a memory area in which the image data to be converted by the electronic device and the converted image data are stored (see Fig.2 (203) and Col.3, Line 32-44).

18. Regarding **Claim 25**, Endo discloses a method of converting image data by use of a plurality of conversion units configured to convert the image data, a control unit configured to control the conversion units (see Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), and



a data communication bus shared among a memory, a processing unit, and the control unit (see Fig.2 (211,201,203,205)), comprising the steps of: receiving image data from the communication bus into the control unit (see Fig.2 (211,101,207,208,209,210)); notifying the control unit of a type of conversion that is to be performed with respect to the image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35); selecting, by the control unit, one of the conversion units in response to the notified type of conversion (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51); supplying, from the control unit, to the multiple conversion units, a signal (command) indicative of a start of transfer of the image data (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50); and transferring the image data from the control unit to the conversion units (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50). Endo fails to disclose selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; and outputting the image data to the communication bus after image data conversions by at least two data conversion units. Mori, however, discloses an image processor for printing image data (see Fig.1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig.1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig.1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig.1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18).

19. Endo and Mori are combinable because they are from the same field of endeavor, namely image data processing methods. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's method of converting image data the steps for selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; and outputting the image data to the communication bus after image data conversions by at least two data conversion units. The motivation would be to convert the image data into a suitable output format for printing in accordance to the type of processing that is to be performed with respect to the image data, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device, based on the type of image data received from the input device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency.

20. Regarding **Claim 26**, the rationale provided for the rejection of Claim 25 is incorporated herein.

21. Regarding **Claim 27**, Endo discloses a method of converting image data by use of a plurality of conversion units configured to convert the image data (see Fig.3 (305,308), Col.3, Line 28-44 and Col.3, Line 57-66), a data communication bus shared among a memory, a processing unit, and the control unit (see Fig.2 (211,201,203,205)), the control unit configured to control the conversion units (see Fig.3 (308) and Col.5, Line 45-53), and a conversion request generating unit configured to request conversion (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35), comprising the steps of: receiving image data from the communication bus

into the control unit (see Fig.2 (211,101,207,208,209,210)); generating, by the conversion request generating unit, information about the type of conversion that is to be performed with respect to the image data (see Fig.9 (\$902,\$903), Col.6, Line 18-28 and Col.6, Line 33-35); instructing, by the conversion request generating unit, the control unit to perform the conversion based on the information (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51); selecting, by the control unit, one of the conversion units in response to the notified type of conversion (see Fig.3 (302,308), Fig.9 (\$909) and Col.6, Line 46-51); supplying, from the control unit to the conversion units, a signal (command) indicative of a start of transfer of the image data (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50); and transferring the image data from the control unit to the conversion units (see Fig.3 (302,308), Fig.9 (\$907,\$909) and Col.5, Line 45-50). Endo fails to disclose selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; and outputting the image data to the communication bus after image data conversions by at least two data conversion units. Mori, however, discloses an image processor for printing image data (see Fig.1 and Col.4, Line 35-41), wherein the image processor includes a first conversion unit for converting image data into a format based on its initial compression format (see Fig.1 (22) and Col.6, Line 31-37), a second conversion unit for converting the color format of the image data into a second color format (see Fig.1 (33) and Col.7, Line 30-37), and a clock unit configured to provide synchronization between the control unit and the two conversion units for transfer of image data (see Fig.1 (30,22,27,33), Col.5, Line 15-30, Col.5, Line 55-59 and Col.6, Line 4-18).

22. Endo and Mori are combinable because they are from the same field of endeavor, namely image data processing methods. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's method of converting image data the steps for selecting at least two conversion units in response to a notified type of conversion; supplying, from the control unit to the selected conversion units, a clock signal that provides synchronization for transfer of the image data; and outputting the image data to the communication bus after image data conversions by at least two data conversion units. The motivation would be to convert the image data into a suitable output format for printing in accordance to the type of processing that is to be performed with respect to the image data, and to regulate the transmission of image data to the image conversion units at a predetermined rate. The compression format and the color format of the image data would allow for the image data to be printed at a specific outputting device, based on the type of image data received from the input device. The synchronizing clock unit can ensure a steady flow of image data to the conversions units for processing efficiency.

23. Regarding **Claim 28**, Endo further discloses a step of notifying, by the control unit, the conversion request generating unit of a completion of the conversion of the image data (see Fig.10B (S1013,S1014) and Col.8, Line 14-22).

24. Claims 8-10 are rejected under 35 U.S.C. 103(a) as being unpatentable over Endo (US Patent 6,801,340 B1) in view of Mori (US Patent 6,965,453 B1), and in further view of Grosse et al. (US Patent 5,636,294).

25. Regarding **Claim 8**, Endo and Mori teach the electronic device as described in Claim 1 but they fail to disclose wherein at least one of the conversion units includes an interruption unit configured to output an interruption signal to the control unit. Grosse, however, discloses an

interruption unit configured to output an interruption signal to the control unit for processing the image data at a predetermined size (see Fig. 15 (454,464,470) and Col. 15, Line 23-36).

26. Endo, Mori and Grosse are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to the conversion units an interruption unit configured to output an interruption signal to the control unit. The motivation would be to process the image data at a predetermined size and rate.

27. Regarding **Claim 9**, Grosse further discloses the interruption unit outputs the interruption signal in response to a completion of conversion of image data that is equal to a predetermined amount (see Fig.15 (454,464,470) and Col.15, Line 23-36).

28. Regarding **Claim 10**, Endo, Mori and Grosse teach the interruption unit of Claim 8 but they fail to expressly disclose that the interruption unit outputs the interruption signal in response to a completion of conversion of image data that is equal in amount to one page of a print sheet. Grosse, however, teaches outputting the interruption signal in response to a completion of conversion of image data that is equal to a predetermined amount (see Fig. 15 (454,464,470) and Col. 15, Line 23-36). At the time of the invention, it would have been obvious for one skilled in the art to include to the interruption unit a means for outputs the interruption signal in response to a completion of conversion of image data that is equal in amount to one page of a print sheet. The motivation would be to process (compress) the image data one page data at a time, since the print data is processed (rasterized) in page by page basis.

29. Claims 3-4, 6-7 and 11 are rejected under 35 U.S.C. 103(a) as being unpatentable over Endo (US Patent 6,801,340 B 1) in view of Mori (US Patent 6,965,453 B1), and in further view of Ohara (US Patent 7,072,060 B2).

30. Regarding **Claim 3**, Endo and Mori teach the apparatus of Claim 1 but they fail to disclose wherein the control unit supplies to one of the conversion units a signal indicating that the image data being transferred is a sub-scan portion of the image data when the sub-scan portion of the image data is being transferred to one of the conversion units. Ohara, however, teaches an image data compression apparatus (see Fig.2 (108,113,115) and Col.5, Line 55 - Col.6, Line 12) wherein the main-scan lines and the sub-scan lines of the image data is read in and processed (see Fig.4A (303,306,308,321) and Col.7, Line 27-42). Ohara further teaches supplying a signal indicating that the image data being transferred and processed is either a sub-scan portion of the image data or a main-scan line portion of the image data (see Fig.4A (303,306,308,321) and Col.7, Line 43-46).

31. Endo, Mori and Ohara are combinable because they are from the same field of endeavor, namely image data processing systems. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a mechanism for supplying to one of the conversion units a signal indicating that the image data being transferred is a sub-scan portion of the image data a main-scan line portion of the image data. The motivation would be to select the appropriate image data conversion engine for the scan line image data. The main-scan lines may require a particular image data conversion engine for processing the main-scan lines, while the sub-scan lines may require a another image data conversion engine that is different. The main-scan lines and sub-scan lines are likely to use

different compression methods and therefore, it would be beneficial to notify the conversion units which scan-line portion of the image data is being transmitted.

32. Regarding **Claim 4**, the rationale provided for the rejection of Claim 3 is incorporated herein.

33. Regarding **Claim 6**, Endo and Mori teach the apparatus of Claim 1 but they fail to disclose wherein one of the conversion units supplies to the control unit a signal indicating that the image data being transferred is a sub-scan portion of the image data when the sub-scan portion of the converted image data is being transferred to the control unit. Ohara, however, teaches an image data compression apparatus (see Fig.2 (108,113,115) and Col.5, Line 55 - Col.6, Line 12) wherein the main-scan lines and the sub-scan lines of the image data is read in and processed (see Fig.4A (303,306,308,321) and Col.7, Line 27-42). Ohara further teaches supplying a signal indicating that the image data being transferred and processed is either a sub-scan portion of the image data or a main-scan line portion of the image data (see Fig.4A (303,306,308,321) and Col.7, Line 43-46).

34. At the time of the invention, it would have been obvious for one skilled in the art to include to Endo's device a mechanism for supplying to the control unit a signal indicating that the image data being transferred is either a sub-scan portion of the converted image data or the main-scan portion of the converted image data. The motivation would be to select the appropriate image data decompression engine for expanding the compressed image data. The main-scan lines and sub-scan lines are likely to use different compression methods. Therefore, it would be beneficial to notify the control units which scan-line portion of the converted image

data is being transmitted in order to send the scan-line portions of the image data to the appropriate decompression engines.

35. Regarding **Claim 7**, the rationale provided for the rejection of Claim 6 is incorporated herein.

36. Regarding **Claim 11**, Endo and Mori teach the device of Claim 8 but they fail to disclose wherein the interruption unit outputs the interruption signal in response to an error occurring during the conversion of the image data. Ohara, however, teaches an interruption unit for outputting the interruption signal in response to detecting the image data amount to be exceeding a limit, and routing the image data to a second compression engine to continue processing (see Fig.2 (108,113,115), Fig.6 (\$505,\$508,\$511) and Col.13, Line 1-24). At the time of the invention, it would have been obvious for one skilled in the art to include to the interruption unit a mechanism for outputting the interruption signal in response to an error occurring during the conversion of the image data. The motivation would be to discontinue the current conversion of the image data and to send a notification to the controller (or display) that an error has occurred.

### ***Conclusion***

37. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

38. A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after



the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

39. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Vu B. Hang whose telephone number is (571)272-0582. The examiner can normally be reached on Monday-Friday, 9:00am - 6:00pm.

40. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David K. Moore can be reached on (571) 272-7437. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

41. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Vu B. Hang/  
Examiner, Art Unit 2625

Application/Control Number: 10/799,707  
Art Unit: 2625

Page 17

/David K Moore/

Supervisory Patent Examiner, Art Unit 2625